

## Tonmind 30W IP Wall Speaker SIP-S11T

1. Transfers especially loud and excellent sound.
2. IP 55 waterproof design for installation on exterior of building.
3. 48K OPUS Audio Codec enables excellent sound quality .
4. Compatible with VoIP, SIP devices (IPPBX, IP Phone) via SIP.
5. Compatible with IP Camera VMS via ONVIF.
6. Support Pre-recorded messages.
7. Support HPPT API for alarm in transmit.



### Specification:

#### Audio

Codec OPUS 48 kHz, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8 kHz, G.711 PCMA 8 kHz

#### Speaker

Max SPL	105dB
Frequency response	80Hz~20KHz
Frequency Range	500-2KHZ +-10dB 400-12KHZ +-20dB
Harmonic Distortion	0.1@1kHz
Signal to Noise Ratio	91dB

#### Network

Security	Password protection, IP address filtering, Digest authentication, User access log, firewall
Network Protocol	SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP
Network Interface	10/100 Base-TX, RJ45
	Support for SIP protocol for intergration with VoIP systems, intergrated with SIP/PBX.
VoIP	2 SIP Accounts, SIP Direct IP Call, RTP Multicast
	Codec: OPUS, MP3, G.722, PCMU, PCMA

#### Amplifier

Amplifier Description	Built-in 30W Amplifier
-----------------------	------------------------

#### General

Operating Temperature	-30°C — +60°C
Operating humidity	5%-85%
Material	ABS (IP55 water-proof)
Rate Power	30W
Power Supply	PoE or 12-24V
Installation	Wall Mounted
Dimensions	296 x 196 x 157 mm
Net Weight	2.5 KG
Languages	English
Warranty	2 years
Package Includes	Network Wall Speaker User Manual