

Tonmind 15W IP Ceiling Speaker SIP-S01

1. Transmit excellent sound for music and announcement.
2. PoE eliminates need for local power supply.
3. 48K OPUS Audio Codec enables excellent sound quality.
4. Compatible with VoIP, SIP devices (IPPBX, IP Phone) via SIP.
5. Compatible with IP Camera VMS via ONVIF.
6. Support Pre-recorded messages.
7. Support HPPT API for alarm in transmit.



Specification:

Audio

Decoding OPUS 48 kHz, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8 kHz, G.711 PCMA 8 kHz

Speaker

Max SPL	96dB
Frequency Response	100Hz ~ 18KHz
Frequency Range	500-2KHZ +-10dB 400-12KHZ +-20dB
Harmonic Distortion	0.1@1kHz
Signal to Noise Ratio	91dB

Network

Security	Password protection, IP address filtering, Digest authentication, User access log, firewall
Network Protocol	SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP
Network Interface	10/100 Base-TX, RJ45
	Support SIP protocol for intergration with VoIP systimes, intergrated with SIP/PBX.
VoIP	Support SIP features: secondary/backend SIP server, IPv4 (IPv6 futhur). Support codecs: OPUS, G711U, G711A, GSM, MP3, WAV.

Amplifier

Amplifier Description Built-in 15W Amplifier

General

Material	Metal
Rate Power	15W
Power Supply	PoE or DC 12V
Installation	In Ceiling
Dimensions	200 x 90 mm
Net Weight	1 KG
Languages	English
Warranty	2 years
Package Includes	Network Ceiling Speaker User Manual